

24" inch Touch Monitor (POS-styler)

Products application :

- POS Terminal
- Industrial PC
- Kiosk
- Gaming
- Medical apparatus
- Personal computer
- Mobile GPS
- Office automation
- Security system of the house
- Car-mounted amusement
- Military equipment
- Communicate



Black : V01W



White : VW01W



24" inch Touch Monitor (POS-styler)

Display Specifications :

Active Area	531 × 298 mm
Pixel Pitch	0.27675 × 0.27675 mm
Brightness	250 cd/m ²
Contrast Ratio	1000 : 1
Resolution	1920 x 1080 (Full HD)
Viewing Angle	L/R 170° ; U/D 160°
Response Time	5 ms (Tr + Tf)
Display Colors	16.7M
Display Modes	640×480 ; 800×600 ; 1024×768 ; 1280×1024 ; 1360×768 ; 1440×900 ; 1680×1050 ; 1920×1080
Signal input	15 Pin D_Sub ; DVI ; Mini-Audio in
Mini-Audio out	2W (8Ω) ×2
OSD Keyboard	⊙Power ⊙Auto adjust ⊕ ⊖ ⊙Menu
Power Source	DC 12V ; ≤23w ; Standby ≤1w
Power Consumption	
Storage	-20~60°C
Operation	0~50°C
VESA	100×100 or 200×100 mm
Casing Colors	Black
Casing Size	575.8 × 344 × 69 mm ; 7.5kg (W×H×D)
Weight	
Carton	670 × 535 × 265 mm ; 11.3kg (W×H×D)
gross weight	



Touch Feature :

Input Method	Finger, gloved hand, or stylus activation
Activation Force	≥50g
Linearity	≤1.5%
Surface	≥3H
Life Time	≤35,000,000
Application	Writing and Signature Capture Capability
PC Link	USB or RS232

Software Feature :

Calibration	Fast full oriental 4 points position
Compensation	Edge compensation. Accuracy 25 points linearity compensation
Draw Test	Position and linearity verification
Controller	Support multiple controllers
Languages	English · Simple Chinese · Traditional Chinese · Japanese · French · German · Spanish · Korean · Arabic · Czech · Danish · Dutch · Greek · Hungarian · Italian · Norwegian · Russian · Polish · Portuguese · Slovenian · Swedish · Thai · Turkish
Mouse Emulator	Right / left button emulation. Auto Right / left Click (PDA function)
Touch Style	Drawing a Mode · button a Mode · Touch Off/ on Switch
Double Click	Configurable double click speed · Configurable double click area
Sound Modes	No sound · Touch down · Touch up
COM Port Support	COM1 ~ COM255 for Windows and Linux COM1 ~ COM8 for MS- DOS
Display Support	display rotation · Support multiple monitors
Support O.S	All Windows-32 bit O.S Windows7-8-10 : XP-64 bit O.S MS-DOS ; A II Linux ; MAC

Order information :

AIM-TM5R240-V01W :	【VGA/AUDIO/DVI/USB-Touch/Black】	AIM-TM5R240-V02W :	【VGA/AUDIO/DVI/RS232-Touch/Black】
AIM-TM5R240-VW01W :	【VGA/AUDIO/DVI/USB-Touch/White】	AIM-TM5R240-VW02W :	【VGA/AUDIO/DVI/RS232-Touch/White】
Accessory	VGA Cable/Power Cable/AC90~260V Adapter/Audio Cable/USB or RS232 Cable/Touch Pen/ Cleaning wipes/Driver Disk※DVI Cable(Optional)		

